

V4000P PROFILE



产品参数

Optical system

Source: OSRAM Lok-it! 1400W/PS

Fixture CT: 6000K

Life span : > 750h

CRI: up to 95

Movement

Pan: 540 ° /630 ° optional(16 bit)

Tilt: 270 ° (16 bit)

Auto X/Y repositioning

Color system

CMY+CTO+CTB color mixing

1 Color wheel: 5 interchangeable dichroic filters + open

Gobo system

2 Rotating gobo wheels: each with 7 interchangeable gobos + open. Gobo OD: 30mm

1 Animation wheel

Effects

Motorized focus

Zoom: 6.8 ° -55 °

Auto focus

1 Rotating prism: 3 facet

Frost

4 individually positionable blades with $\pm 45^\circ$ rotation of the complete framing system

Iris

Dimming: 0-100% linear dimming

Shutter: mechanical with various speed

Protection rating

IP20

Display

Battery operated for fast addressing, 15 seconds standby auto lock

Pan/tilt disengage (hold Left arrow and Right arrow buttons)

Software

Upgrade with DMX or USB as optional

Remote reset DMX address and fixture by DMX

Run time of fixture and light source

3 Control channel modes: 40/38/62CH

Control

Input signal isolation
Auto thermal protection circuit
Art-Net control
RDM compatible

Electric parameter
AC100-240V, 50/60Hz
Power: 1800W

Dimension and weight
Product dimension: 46.7x36.8x82.1cm
Packing dimension (carton): 94.5x58.0x50.5cm
Net weight: 43.0kgs
Gross weight (carton): 49.5kgs