

## G6H NOVA HYBRID



### 产品参数

#### Optical system

Source: Philips MSD Platinum Flex 200, 280W

Fixture CT: 8000K

Life span : 6,000h

Fixture output: 11,500lm

#### Movement

Pan: 540 ° /630 ° optional(16 bit)

Tilt: 270 ° (16 bit)

Auto X/Y repositioning

#### Color system

## CMY color mixing

1 Color wheel: 13 dichroic filters + open

## Gobo system

1 Rotating gobo wheel: 8 interchangeable gobos + open. Gobo OD: 14mm

1 Static gobo wheel: 12 indexable gobos + open

## Effects

### Motorized focus

Zoom: beam mode:  $1.9^{\circ}$  -  $19^{\circ}$  , spot mode:  $2.6^{\circ}$  -  $27^{\circ}$  , wash mode:  
 $3.6^{\circ}$  -  $25^{\circ}$

### Auto focus

2 Rotating prisms: 4 linear + 16 facet, dynamic prism morph

### Frost

Dimming: 0-100% linear dimming

Shutter: mechanical with various speed

## Protection rating

IP20

## Display

Battery operated for fast addressing, 15 seconds standby auto lock

Pan/tilt disengage (hold Left arrow and Right arrow buttons)

## Software

Upgrade with DMX

Remote reset DMX address and fixture by DMX

Run time of fixture and light source

3 Control channel modes: 22/24/34CH

## Control

Input signal isolation

Auto thermal protection circuit

Optional installed wireless receiver

Art-Net control  
RDM compatible

Electric parameter  
AC100-240V, 50/60Hz  
Power: 480W

Dimension and weight  
Product dimension: 38.6x30.2x66.2cm  
Packing dimension (carton): 78.5x50.5x44.5cm  
Net weight: 23.8kgs  
Gross weight (carton): 29.0kgs