GL6 IP LED PROFILE



Product parameters

Optical system
Source: 580W White LED
Fixture CT: 6500K
Life span：>20,000h
CRI: ≥72 (GL6H IP: up to 90)
Fixture output: 35,500lm

Movement
Pan: 540 ° /630 ° optional(16 bit)
Tilt: 270 ° (16 bit)
Auto X/Y repositioning

Color system
CMY+CTO+CTB color mixing
1 Color wheel: 5 dichroic filters + open

Gobo system
2 Rotating gobo wheels: wheel 1: 6 interchangeable + open,Gobo OD: 34mm; wheel 2: 7 interchangeable + open, Gobo OD: 27mm
1 Static gobo wheel: 7 gobos + open
1 Animation wheel

Effects
Motorized focus
Zoom: 6 ° - 52 °
Auto focus
2 Rotating prisms: 4 linear+ 4 facet prism
Frost: light frost, heavy frost， various frost effect
4 individually positionable blades with ±45 ° rotation of the complete framing system
Iris
Dimming: 0-100% linear dimming
Strobe: electronic, variable from 1-25Hz or pulse

Protection rating
IP65

Display
Battery operated for fast addressing,15 seconds standby auto lock
Pan/ Tilt disengage (hold LEFT and RIGHT button)

Software
Upgrade with DMX
Remote reset DMX address, fixture reset by DMX
Run time of light source and fixture
3 Control channel modes: 45/43/69 CH

Control

Input signal isolation
Art-Net control
RDM compatible
Electric parameter
AC100-240V, 50/60Hz
Power: 1000W

Dimension and weight

Product dimension：46.8x37.0x67.7cm
Packing dimension（carton）：80.5x57.0x50.5cm
Net weight：41kgs
Gross weight（carton）：47.5kgs

Patent

Patented: 3 gobo wheels plus 1 animation wheel structure


Colours/ Gobos


COLOR WHEEL: 


:

ROTATING GOBO WHEEL I: 


Dimensions








Photometrics





Errors and omissions are possible. All specifications are subject for change without prior notice.