

## BPAR5QB-R LED PAR



### 产品参数

#### Optical system

Source: 5 x 15W RGBW LED

Life span : >50,000h

Fixture output: 2,100lm

#### Color system

RGBW color mixing

#### Effects

Zoom: 7 ° (beam angle), 18 ° (field angle)

Dimming: 0-100% linear dimming

Strobe: electronic, variable from 1-25Hz or pulse

Protection rating  
IP65

Display  
Battery operated for fast addressing, 15 seconds standby auto lock

Software  
Upgrade with DMX  
Remote reset DMX address and fixture by DMX  
Run time of fixture and light source  
4 Control channel modes: 4/5/11/12CH

Control  
Input signal isolation  
Installed wireless receiver  
RDM compatible

Electric parameter  
AC100-240V, 50/60Hz  
Power: 70W  
Power supply: battery or DC mains  
Battery usage time: 7 hrs (at full power), 19 hrs (when color changing)  
Battery charge time: 8 hrs (when connected to mains)  
Replaceable battery

Dimension and weight  
Product dimension: 29.0x25.1x28.8cm  
Packing dimension (carton): 39.0x36.5x38.5cm  
Net weight: 6.8kgs  
Gross weight (carton): 11.0kgs

Others  
Flight case: with charging status windows and 6 charging bases. Operating

temperature: -10 ° C to 45 ° C. Flight case net weight: 40.2kgs  
Optional six in one flight case with charger base  
Aluminum die-cast housing