Outdoor Graze ELV-G2 DMX



Product parameters

The DynaGraze Exterior HO DMX is a high power, outdoor linear fixture. Available in1'and 4' sections, featuring a robust IP67 housing, a multi-voltage switching power supply, and a glare shield, it is the perfect option for any structure that calls for outdoor linear grazing.

Color Temperature: 2700K, 3000K, 3500K, 4000K
Beam Angle: 10 ° X 10 ° ,10 ° X 60 ° ,30 ° X 60 °
Max Fixture Runs: 50
Power Consumption: 34W
Total Lumens: 1500lm@3500K
Efficacy (lm/W): 44lm/W@3500K
CRI: >80

Finish: Anodized Brushed Aluminum (Black or White - Special Order Only)
Housing: Aluminum; Clear Polycarbonate Lens
Operating Temperature: -20 ° C to 45 ° C
Operating Voltage: 100-240V
Dimming: DMX 512
Fixture Connectors:Integral, 8 Pin Male & Female Connector
Rating: IP 67
Weight: 3.3kg
Dimensions: 609.4mmx74.1mmx90mm

Colours/ Gobos


:

:

:

Dimensions

Guangzhou Haoyang Electronic Co., Ltd.
Address: No. 18, the First Crossroad of Lianyun Road, Shiqi Town, Panyu District, Guangzhou.
TEL:+86 2039966388/39966399 FAX:+86 2039966388/39966399
Email: www.terbly.com Website: sales@teroly.com



Errors and omissions are possible. All specifications are subject for change without prior notice.