

---

## CABINET SCREEN GS-P3.9



### Product parameters

Our GS-P3.9 is designed for indoor use LED die cast screen. Its cabinet specially is made of aluminum die casting, which guarantee whole LED screen portable and durable use. GS-P3.9 uses Golden sea self-developed HDMI control system and is compatible to any DMX controller. Optional choice is traditional Gigabit Ethernet control system. Seamless mechanical system and easy for maintenance and high contrast levels. Support a refresh rate over 4000Hz for flicker free application and 16-bit processing.

### SPECIFICATIONS

Pixel Pitch:3.9mm

Pixel Density:65536dot/m<sup>2</sup>



---

Panel Size:500x500x84mm  
Panel Weigh:10.3kg  
LED Type:SMD2121  
Brightness:1200CD/m<sup>2</sup>  
Viewing Angle:H120 ° / V120 °  
Scanning Rate:50/60Hz  
Refresh Rate 4000Hz  
Contrast Level:2000:1  
Gray Scale:16 Bits  
Life Span:100000H  
IP Rating :IP20  
Max Power:600W/m<sup>2</sup>  
Ave Power:300W/m<sup>2</sup>  
Operating Temperature:-30 ~+50  
Operating Humidity:10%-90%

## Colours/ Gobos

:

:

:

Errors and omissions are possible. All specifications are subject for change without prior notice.