

GLW1940 IP

SMART Defender



Product parameters

Optical system

Source: 19x40W RGBL(L for lime) LED (optional RGBW or RGBA)

Light source life expectancy : 50,000 hours Average Light Source Life*

Movement

Pan: 540 ° (16 bit)

Tilt: 270 ° (16 bit)

Auto X/Y repositioning

Color system

RGBL color mixing

Color temperature linear: 2700K to 8000K , Color temperature presets:
2700K,3200K,4300K,5600K,6500K,8000K

Effects

Zoom range: 4.5 ° -29 ° (beam angle) , 5.7 ° -55 ° (field angle)

Dimming: 0-100% linear dimming

Strobe: electronic, variable from 1-25Hz or pulse

Pixel Control

GAMMA: 2.0, 2.2, 2.4, 2.6, 2.8, to fit different cameras' linearity

Refresh rate: 900Hz-25,000Hz

Protection rating

IP66

Display

Battery operated for fast addressing,45 seconds standby auto lock

Software

Upgrade with DMX

Remote reset DMX address and fixture by DMX

Run time of light source and fixture

2 Control channel modes: 25/95CH

Auto thermal protection circuit

Control

Input signal isolation

Optional Art-Net control

RDM protocol

Electric parameter

AC200-240V, 50/60Hz

Power: 850W

Dimension and weight

Product dimension: 270x395x472mm

Net weight: 18kg

*Testing conditions in the lab may differ based on various factors.

Colours/ Gobos

:

:

:

Errors and omissions are possible. All specifications are subject for change without prior notice.