
WATERPROOF DOME WP08



Product parameters

Wp08 is suitable for most high power moving heads up to 1500W, 2000W like Terbly's V1500, V2000, V3000 series.

Being more resistant to high temperature, more durable and more economical, it can effectively protect fixtures from the erosion of rain water and humidity in the outdoor performance.

The dome could be separated from the base during transportation.

Waterproof : IP54

Dome: new type of UV-resistant and heat-resistant PC material

Base: stainless steel material, matte black finish

Installation: 360 ° hung and fixed by 4pcs of M12 screws or positioned on the floor



High effective transmission: over 82%

Outdoor ambience:0-45 °

Temperature : -20 ° to 45 °

Humidity:0-100%

Excellent air circulation system well control temperature and humidity

Cooling: the dome and protected fixture are connected by different power supply, allowing the dome to keep cooling down after the protected fixture is off.

Control: RDM compatible; the display shows humidity, and working state

Connection: Powercon plug inside for corresponding fixture; DMX control between the dome and protected fixture;

Wireless for option

Power: AC110~120V or AC220~240V 50/60HZ

Max. output power: 2000W

Max. load: 100kgs

Net weight: 62.5kgs

Standard Accessories

Omega clamps:2 sets

Safety cord:2 pcs

Colours/ Gobos

:

:

:



Errors and omissions are possible. All specifications are subject for change without prior notice.